68A200Z1-0002

series: Tube lights Tube lights

Type of installation:	Ceiling mounting, pendant, Wall (surface)
Type of Protection:	IP 67
Protection class:	I
Lamp:	LED
Dimensions:	D 79, L 685
Colour:	grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 cable entries (through-wiring), incl. LED panel

electro-technics:

System power	21 W
Electric Gear	Converter
Voltage	220 - 240 V / 50 Hz, 60 Hz

Spezifikationen:

Lamp cover	opal

testings:

Type of Protection	IP 67
Protection class	I
Filament test	850°C - 30 seconds
Impact resistance	IK08
Safety Marks	F-mark
Other Marks	WEEE mark
Country Code	Made in Germany

lamp 1:

Lamp	LED
Rated luminous flux	3200 lm
Number of Lamps	2
Colour Temperature	5000 K
Colour rendering index (CRI)	80
Lifespan	50000 h (L90/B50)

weights and measures:

Length L	685 mm
Diameter D	79 mm
Weight	1,53 kg

accessories

68Z00001	Mounting bracket (plastic) grey
68Z00002	Mounting bracket (metal) with magnet zinc plated
68Z00003	Mounting bracket (plastic) with magnet grey
68Z00007	Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated
68Z00004	Mounting bracket (metal) with hanger assembly of stainless steel zinc plated
68Z00016	Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey
68Z00006	Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated
68Z00017	Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey
68Z00005	Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated
68Z00008	Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey