



# 68A20106-0062



series: Tube lights Tube lights

Type of installation: Universal mounting system  
 Type of Protection: IP 44  
 Protection class: I  
 Lamp: LED  
 Dimensions: D 120, L 750  
 Colour: grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 protectors blue, socket, power supply cable with mains plug, incl. LED panel

### electro-technics:

Electric Gear Converter  
 System Power 23 W  
 Voltage 220 - 240 V / 0 Hz, 50 - 60 Hz

### Spezifikationen:

Colour TPE blue  
 Power supply cable H07RN-F  
 Size power supply cable 3 x 1,5 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Connector systems CEE-6h  
 Socket outlets 1  
 Lamp cover opal

### testings:

Type of Protection IP 44  
 Protection class I  
 Filament test 650°C - 30 seconds  
 Impact resistance IK08 (5 Joule)  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

### lamp 1:

Lamp LED  
 Number of Lamps 2  
 Wattage 14,00 W  
 Socket without socket  
 Colour Temperature 5000 K  
 Colour rendering index (CRI) 80  
 Lifespan 50000 h (L90/B50)

### weights and measures:

Length L 750 mm  
 Diameter D 120 mm  
 Weight 2,5 kg

### lighting technology:

Luminaire flux 2.600 lm

### accessories

- 68Z00001 Mounting bracket (plastic) grey
- 68Z00002 Mounting bracket (metal) with magnet zinc plated
- 68Z00003 Mounting bracket (plastic) with magnet grey
- 68Z00007 Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated
- 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel zinc plated
- 68Z00016 Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey
- 68Z00006 Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated
- 68Z00017 Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey
- 68Z00005 Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated
- 68Z00008 Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey