



# 68A250Z1-0002



series: Tube lights Tube lights

Type of installation: Ceiling mounting, pendant, Wall (surface)  
 Type of Protection: IP 67  
 Protection class: III  
 Lamp: LED  
 Dimensions: D 79, L 685  
 Colour: grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 cable entries (through-wiring), incl. LED panel

## electro-technics:

System power 21 W  
 Electric Gear Converter  
 Voltage 24 V / 50 Hz

## Spezifikationen:

Lamp cover opal

## testings:

Type of Protection IP 67  
 Protection class III  
 Filament test 850°C - 30 seconds  
 Impact resistance IK08  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

## lamp 1:

Rated luminous flux 3200 lm  
 Lamp LED  
 Number of Lamps 2  
 Colour Temperature 5000 K  
 Colour rendering index (CRI) 80  
 Lifespan 50000 h (L70/B50)

## weights and measures:

Length L 685 mm  
 Diameter D 79 mm  
 Weight 1,46 kg

## accessories

68Z00001 Mounting bracket (plastic) grey  
 68Z00002 Mounting bracket (metal) with magnet zinc plated  
 68Z00003 Mounting bracket (plastic) with magnet grey  
 68Z00007 Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated  
 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel zinc plated  
 68Z00016 Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey  
 68Z00006 Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated  
 68Z00017 Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey  
 68Z00005 Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated  
 68Z00008 Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey