


68A3000C-0062

series: Schutzrohrleuchten Chain



Type of installation: Ceiling mounting, pendant, Wall (surface)
 Type of Protection: IP 67
 Protection class: II
 Lamp: LED
 Dimensions: D 120, L 965
 Colour: grey

Protective tube luminaire for use in a luminaire chain. Protective tube made of impact-resistant opal plastic (polycarbonate). Plastic end caps (gray/polyamide). Integrated control gear. 2 protectors (blue). 5 m supply cable (H07RN-F) with RST16 plug. 0.3 m cable with RST16 socket. Extensive range of optional accessories for suspension or mounting. A mains cable is required for operation (see accessories).

electro-technics:

Electric Gear	Converter
System Power	33 W
Voltage	220 - 240 V / 50 Hz, 60 Hz

Spezifikationen:

Colour TPE	blue
Power supply cable	H07RN-F
Size power supply cable	3 x 1,5 mm ²
Length power supply cable	5 m
Colour power supply cable	black
Lamp cover	opal
Connector systems	Wieland RST mini

testings:

Type of Protection	IP 67
Protection class	II
Filament test	850 °C
Impact resistance	IK08
Safety Marks	F-mark
Other Marks	WEEE mark
Country Code	Made in Germany

lamp 1:

Lamp	LED
Number of Lamps	3
Wattage	14,00 W
Socket	without socket
Colour Temperature	5000 K
Colour rendering index (CRI)	80
Lifespan	50000 h (L80/B50)

weights and measures:

Length L	965 mm
Diameter D	120 mm
Weight	3,16 kg

accessories

95-000C-0001 Power supply cable with plug (type E+F, CEE7/7) and on/off switch black
 95-010C-0001 Power supply cable with plug (type E+F, CEE7/7, IP68) and on/off switch black
 95-060C-0001 Power supply cable with plug (CEE 6h, 16A, blue) and on/off switch black
 95-0C0C-0001 Power supply extension, Chain 230 V black