


# 68A3000C-0062

series: Schutzrohrleuchten Chain



Type of installation: Ceiling mounting, pendant, Wall (surface)  
 Type of Protection: IP 67  
 Protection class: II  
 Lamp: LED  
 Dimensions: D 120, L 965  
 Colour: grey

Protective tube luminaire for use in a luminaire chain. Protective tube made of impact-resistant opal plastic (polycarbonate). Plastic end caps (gray/polyamide). Integrated control gear. 2 protectors (blue). 5 m supply cable (H07RN-F) with RST16 plug. 0.3 m cable with RST16 socket. Extensive range of optional accessories for suspension or mounting. A mains cable is required for operation (see accessories).

## electro-technics:

System power 31 W  
 Electric Gear Converter  
 Voltage 220 - 240 V / 50 Hz, 60 Hz

## Spezifikationen:

Colour TPE blue  
 Power supply cable H07RN-F  
 Size power supply cable 3 x 1,5 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Connector systems Wieland RST mini  
 Lamp cover opal

## testings:

Type of Protection IP 67  
 Protection class II  
 Filament test 850 °C  
 Impact resistance IK08  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

## lamp 1:

Rated luminous flux 5100 lm  
 Lamp LED  
 Number of Lamps 3  
 Colour Temperature 5000 K  
 Colour rendering index (CRI) 80  
 Lifespan 50000 h (L90/B50)

## weights and measures:

Length L 965 mm  
 Diameter D 120 mm  
 Weight 3,16 kg

## accessories

- 95-000C-0001 Power supply cable with plug (type E+F, CEE7/7) and on/off switch black
- 95-010C-0001 Power supply cable with plug (type E+F, CEE7/7, IP68) and on/off switch black
- 95-060C-0001 Power supply cable with plug (CEE 6h, 16A, blue) and on/off switch black
- 95-0C0C-0001 Power supply extension, Chain 230 V black