



# 68A3000C-0072.NL



series: Schutzrohrleuchten Chain

Type of installation: Ceiling mounting, pendant, Wall (surface)  
 Type of Protection: IP 67  
 Protection class: II  
 Lamp: LED  
 Dimensions: D 120, L 1000  
 Colour: grey

Protective tube luminaire for use in a luminaire chain. Protective tube made of impact-resistant opal plastic (polycarbonate). Plastic end caps (gray/polyamide). Integrated control gear. 2 protectors (green). 5 m supply cable (H07RN-F) with RST16 plug. 0.3 m cable with RST16 socket. Extensive range of optional accessories for suspension or mounting. Integrated rechargeable battery. Emergency lighting function with reduced luminaire luminous flux for max. 120 min. with fully charged battery. 3 emergency light cycles of 60 min. each possible with full battery. Emergency function can be deactivated for transportation or storage. A mains cable is required for operation (see accessories).

## electro-technics:

Electric Gear	Converter
System Power	24 W
Voltage	220 - 240 V / 50 Hz, 60 Hz

## Spezifikationen:

Colour TPE	grün
Power supply cable	H07RN-F
Size power supply cable	3 x 1,5 mm <sup>2</sup>
Length power supply cable	5 m
Colour power supply cable	black
Additional functions	with 'TNF'
Lamp cover	opal
Connector systems	Wieland RST mini

## testings:

Type of Protection	IP 67
Protection class	II
Filament test	850 °C
Impact resistance	IK08
Safety Marks	D-mark, F-mark
Other Marks	WEEE mark
Country Code	Made in Germany

## lamp 1:

Lamp	LED
Number of Lamps	3
Wattage	14,00 W
Socket	without socket
Colour Temperature	5000 K
Colour rendering index (CRI)	80
Lifespan	50000 h (L80/B50)

## weights and measures:

Length L	1.000 mm
Diameter D	120 mm
Weight	3,64 kg

## accessories

95-000C-0001 Power supply cable with plug (type E+F, CEE7/7) and on/off switch black  
 95-010C-0001 Power supply cable with plug (type E+F, CEE7/7, IP68) and on/off switch black  
 95-060C-0001 Power supply cable with plug (CEE 6h, 16A, blue) and on/off switch black  
 95-0C0C-0001 Power supply extension, Chain 230 V black