



# 68A30101-0062.NL



series: Tube lights

Type of installation: Ceiling mounting, pendant, Wall (surface)  
 Type of Protection: IP 65  
 Protection class: I  
 Lamp: LED  
 Dimensions: D 120, L 1030  
 Colour: grey

LED-Schutzrohrleuchte, Schutzrohr aus schlagfestem Kunststoff opal (Polycarbonat), Endkappen aus Kunststoff grau (Polyamid), Betriebsgerät integriert, 2 Protektoren (blau), 1 Steckdose, Zuleitung mit Netzstecker, max. 2 Stunden Notlicht (800 lm) bei Stromausfall, ausschaltbar per Taster

## electro-technics:

System power 24 W  
 Electric Gear Converter  
 Voltage 220 - 240 V / 50 Hz, 60 Hz

## Spezifikationen:

Colour TPE blue  
 Power supply cable H07RN-F  
 Size power supply cable 3 x 1,5 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Additional functions with 'TNF'  
 Socket outlets 1  
 Connector systems Typ F, Schuko IP68 (CEE 7/4)  
 Lamp cover opal

## testings:

Type of Protection IP 65  
 Protection class I  
 Filament test 650 °C  
 Impact resistance IK08  
 Other Marks WEEE mark  
 Country Code Made in Germany

## lamp 1:

Rated luminous flux 3400 lm  
 Lamp LED  
 Number of Lamps 3  
 Colour Temperature 5000 K  
 Colour rendering index (CRI) 80  
 Lifespan 50000 h (L90/B50)

## weights and measures:

Length L 1.030 mm  
 Diameter D 120 mm  
 Weight 3,55 kg

## accessories

68Z00001 Mounting bracket (plastic) grey  
 68Z00002 Mounting bracket (metal) with magnet zinc plated  
 68Z00003 Mounting bracket (plastic) with magnet grey  
 68Z00007 Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated  
 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel zinc plated  
 68Z00016 Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey  
 68Z00006 Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated  
 68Z00017 Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey  
 68Z00005 Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated  
 68Z00008 Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey