



# 68A350Z1-0002



series: Tube lights Tube lights

Type of installation: Universal mounting system  
 Type of Protection: IP 67  
 Protection class: III  
 Lamp: LED  
 Dimensions: D 120, L 965  
 Colour: grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 protectors blue, power supply cable with mains plug, incl. LED panel

## electro-technics:

Electric Gear Converter  
 System Power 35 W  
 Voltage 24 V / 50 - 60 Hz

## Spezifikationen:

Power supply cable H07RN-F  
 Size power supply cable 2 x 1,5 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Connector systems CEE 24VAC  
 Lamp cover opal

## testings:

Type of Protection IP 67  
 Protection class III  
 Filament test 850°C - 30 seconds  
 Impact resistance IK10 (20 Joule)  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

## lamp 1:

Lamp LED  
 Number of Lamps 3  
 Wattage 14,00 W  
 Socket without socket  
 Colour Temperature 5000 K  
 Colour rendering index (CRI) 80  
 Lifespan 50000 h (L70/B50)

## weights and measures:

Length L 965 mm  
 Diameter D 120 mm  
 Weight 2,096 kg

## lighting technology:

Luminaire flux 3.900 lm

## accessories

68Z00001 Mounting bracket (plastic) grey  
 68Z00002 Mounting bracket (metal) with magnet zinc plated  
 68Z00003 Mounting bracket (plastic) with magnet grey  
 68Z00007 Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated  
 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel zinc plated  
 68Z00016 Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey  
 68Z00006 Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated  
 68Z00017 Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey  
 68Z00005 Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated  
 68Z00008 Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey