


# 68A3610C-0062

series: Schutzrohrleuchten Chain



Type of installation: Ceiling mounting, pendant, Wall (surface)  
 Type of Protection: IP 67  
 Protection class: III  
 Lamp: LED  
 Dimensions: D 120, L 965  
 Colour: grey

Protective tube luminaire for use in a luminaire chain. Protective tube made of impact-resistant opal plastic (polycarbonate). Plastic end caps (gray/polyamide). Integrated control gear. 2 protectors (blue). 5 m supply cable (H07RN-F) with RST16 plug. 0.3 m cable with RST16 socket. Extensive range of optional accessories for suspension or mounting. A mains cable is required for operation (see accessories).

## electro-technics:

Electric Gear	Converter
System Power	35 W
Voltage	42 V / 50 Hz, 60 Hz

## Spezifikationen:

Colour TPE	blue
Power supply cable	H07RN-F
Size power supply cable	3 x 2,5 mm <sup>2</sup>
Length power supply cable	5 m
Colour power supply cable	black
Lamp cover	opal
Connector systems	Wieland RST mini

## testings:

Type of Protection	IP 67
Protection class	III
Filament test	850 °C
Impact resistance	IK08
Safety Marks	F-mark
Other Marks	WEEE mark
Country Code	Made in Germany

## lamp 1:

Lamp	LED
Number of Lamps	3
Wattage	14,00 W
Socket	without socket
Colour Temperature	5000 K
Colour rendering index (CRI)	80
Lifespan	50000 h (L80/B50)

## weights and measures:

Length L	965 mm
Diameter D	120 mm
Weight	3,04 kg

## accessories

95-600C-0001 Power supply cable with plug (CEE 42V~) and on/off switch black  
 95-6C0C-0001 Power supply extension, Chain 230 V black