



# 68A36160-0062



series: Tube lights Tube lights

Type of installation: Ceiling mounting, pendant, Wall (surface)  
 Type of Protection: IP 44  
 Protection class: III  
 Lamp: LED  
 Dimensions: D 120, L 1041  
 Colour: grey

Protective tube plastic opal (polycarbonate), end caps plastic grey (polyamide), integrated electronic driver, 2 protectors blue, socket, power supply cable with mains plug, incl. LED panel

### electro-technics:

System power 35 W  
 Electric Gear Converter  
 Voltage 42 V / 50 Hz, 60 Hz

### Spezifikationen:

Colour TPE blue  
 Power supply cable H07RN-F  
 Size power supply cable 2 x 1,5 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Socket outlets 1  
 Connector systems CEE 42VAC  
 Lamp cover opal

### testings:

Type of Protection IP 44  
 Protection class III  
 Filament test 650°C - 30 seconds  
 Impact resistance IK08 (5 Joule)  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

### lamp 1:

Rated luminous flux 5000 lm  
 Lamp LED  
 Number of Lamps 3  
 Colour Temperature 5000 K  
 Colour rendering index (CRI) 80  
 Lifespan 50000 h (L90/B50)

### weights and measures:

Length L 1,041 mm  
 Diameter D 120 mm  
 Weight 2,57 kg

### accessories

- 68Z00001 Mounting bracket (plastic) grey
- 68Z00002 Mounting bracket (metal) with magnet zinc plated
- 68Z00003 Mounting bracket (plastic) with magnet grey
- 68Z00007 Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated
- 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel zinc plated
- 68Z00016 Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey
- 68Z00006 Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated
- 68Z00017 Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey
- 68Z00005 Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated
- 68Z00008 Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey