



68A46160-0062.NL



series: Tube lights emergency light Tube lights

Type of installation: Ceiling mounting, pendant, Wall (surface)
 Type of Protection: IP 44
 Protection class: III
 Lamp: LED
 Dimensions: D 120, L 1363
 Colour: grey

LED protective tube luminaire, protective tube of impact-resistant plastic opal (polycarbonate), end caps of plastic grey (polyamide), control gear integrated, 2 protectors (blue), 1 socket, supply cable with mains plug, emergency light operation in case of power failure with 400 lm, maximum for 60 minutes, full battery capacity is sufficient for a maximum of 3 emergency light cycles, can be switched off by pushbutton

electro-technics:

Electric Gear Converter
 System Power 51 W
 Voltage 42 V / 50 Hz, 60 Hz

Spezifikationen:

Colour TPE blue
 Power supply cable H07RN-F
 Size power supply cable 2 x 1,5 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Connector systems CEE 42VAC
 Socket outlets 1
 Lamp cover opal

testings:

Type of Protection IP 44
 Protection class III
 Filament test 850 °C
 Impact resistance IK08
 Other Marks WEEE mark
 Country Code Made in Germany

lamp 1:

Lamp LED
 Number of Lamps 4
 Wattage 14,00 W
 Socket without socket
 Colour Temperature 5000 K
 Colour rendering index (CRI) 80
 Lifespan 50000 h (L90/B50)

weights and measures:

Length L 1.363 mm
 Diameter D 120 mm
 Weight 3,4 kg

lighting technology:

Luminaire flux 5.600 lm

accessories

68Z00001 Mounting bracket (plastic) grey
 68Z00002 Mounting bracket (metal) with magnet zinc plated
 68Z00003 Mounting bracket (plastic) with magnet grey
 68Z00007 Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated
 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel zinc plated
 68Z00016 Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey
 68Z00006 Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated
 68Z00017 Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey
 68Z00005 Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated
 68Z00008 Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey