

# 68E10100-0062

series: Tube lights Basic



Type of installation: Ceiling mounting, pendant, Wall (surface)  
 Type of Protection: IP 54  
 Protection class: I  
 Lamp: LED  
 Dimensions: D 120, L 788  
 Colour: grey

Protective tube light 'Basic'. Protection tube plastic (polycarbonate) opal, shockproof. End caps made of plastic (polyamide) grey. Protectors made of soft plastic at the ends for protection during mobile use. Uniform, soft and glare-reduced illumination. Driver integrated. A socket outlet enables the connection of additional luminaires or electrical devices. Heavy rubber power supply cable H07RN-F for high mechanical loads with mains plug. Suitable for wall, ceiling and pendant mounting due to accessories (optional).

## electro-technics:

System power 30 W  
 Electric Gear Converter  
 Voltage 220 - 240 V / 50 Hz, 60 Hz

## Spezifikationen:

Colour TPE blue  
 Power supply cable H07RN-F  
 Size power supply cable 3 x 1,5 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Socket outlets 1  
 Connector systems Typ F, Schuko (CEE 7/4)  
 Lamp cover opal

## testings:

Type of Protection IP 54  
 Protection class I  
 Filament test 850 °C  
 Impact resistance IK08 (5 Joule)  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

## lamp 1:

Rated luminous flux 3450 lm  
 Lamp LED  
 Number of Lamps 1  
 Colour Temperature 4000 K  
 Colour rendering index (CRI) 80  
 Lifespan 72000 h (L80/B50)

## weights and measures:

Length L 788 mm  
 Diameter D 120 mm  
 Weight 2,143 kg

## accessories

68Z00001 Mounting bracket (plastic) grey  
 68Z00002 Mounting bracket (metal) with magnet zinc plated  
 68Z00003 Mounting bracket (plastic) with magnet grey  
 68Z00007 Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated  
 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel zinc plated  
 68Z00016 Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey  
 68Z00006 Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated  
 68Z00017 Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey  
 68Z00005 Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated  
 68Z00008 Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey