



68E20100-0062



series: Tube lights Basic

Type of installation: Ceiling mounting, pendant, Wall (surface)
 Type of Protection: IP 54
 Protection class: I
 Lamp: LED
 Dimensions: D 120, L 1346
 Colour: grey

Protective tube light 'Basic'. Protection tube plastic (polycarbonate) opal, shockproof. End caps made of plastic (polyamide) grey. Protectors made of soft plastic at the ends for protection during mobile use. Uniform, soft and glare-reduced illumination. Driver integrated. A socket outlet enables the connection of additional luminaires or electrical devices. Heavy rubber power supply cable H07RN-F for high mechanical loads with mains plug. Suitable for wall, ceiling and pendant mounting due to accessories (optional).

electro-technics:

System power 37 W
 Electric Gear Converter
 Voltage 220 - 240 V / 50 Hz, 60 Hz

Spezifikationen:

Colour TPE blue
 Power supply cable H07RN-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Socket outlets 1
 Connector systems Typ F, Schuko (CEE 7/4)
 Lamp cover opal

testings:

Type of Protection IP 54
 Protection class I
 Filament test 850 °C
 Impact resistance IK08 (5 Joule)
 Safety Marks F-mark
 Other Marks WEEE mark
 Country Code Made in Germany

lamp 1:

Rated luminous flux 5200 lm
 Lamp LED
 Number of Lamps 1
 Colour Temperature 4000 K
 Colour rendering index (CRI) 80
 Lifespan 72000 h (L80/B50)

weights and measures:

Length L 1,346 mm
 Diameter D 120 mm
 Weight 2,952 kg

accessories

68Z00001 Mounting bracket (plastic) grey
 68Z00002 Mounting bracket (metal) with magnet zinc plated
 68Z00003 Mounting bracket (plastic) with magnet grey
 68Z00007 Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated
 68Z00004 Mounting bracket (metal) with hanger assembly of stainless steel zinc plated
 68Z00016 Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey
 68Z00006 Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated
 68Z00017 Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey
 68Z00005 Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated
 68Z00008 Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey