


68E201B0-0062

series: Tube lights Basic



Type of installation: Ceiling mounting, pendant, Wall (surface)
 Type of Protection: IP 54
 Protection class: I
 Lamp: LED
 Dimensions: D 120, L 1331
 Colour: grey

Protective tube light 'Basic'. Protection tube plastic (polycarbonate) opal, shockproof. End caps made of plastic (polyamide) grey. Protectors made of soft plastic at the ends for protection during mobile use. Uniform, soft and glare-reduced illumination. Driver integrated. A socket outlet enables the connection of additional luminaires or electrical devices. Heavy rubber power supply cable H07RN-F for high mechanical loads with mains plug. Suitable for wall, ceiling and pendant mounting due to accessories (optional).

electro-technics:

Electric Gear	Converter
System Power	37 W
Voltage	220 - 240 V / 50 Hz, 60 Hz

Spezifikationen:

Colour TPE	blue
Power supply cable	H07RN-F
Size power supply cable	3 x 1,5 mm ²
Length power supply cable	5 m
Colour power supply cable	black
Connector systems	Typ E (CEE 7/5)
Socket outlets	1
Lamp cover	opal

testings:

Type of Protection	IP 54
Protection class	I
Filament test	850 °C
Impact resistance	IK08 (5 Joule)
Safety Marks	F-mark
Other Marks	WEEE mark
Country Code	Made in Germany

lamp 1:

Lamp	LED
Number of Lamps	1
Wattage	28,80 W
Socket	without socket
Colour Temperature	4000 K
Colour rendering index (CRI)	80
Lifespan	72000 h (L80/B50)

weights and measures:

Length L	1.331 mm
Diameter D	120 mm
Weight	2,952 kg

accessories

68Z00001	Mounting bracket (plastic) grey
68Z00002	Mounting bracket (metal) with magnet zinc plated
68Z00003	Mounting bracket (plastic) with magnet grey
68Z00007	Magnetic holder, mounting bracket (plastic) with rubberised magnet, set (2 pieces) zinc plated
68Z00004	Mounting bracket (metal) with hanger assembly of stainless steel zinc plated
68Z00016	Mounting bracket (plastic) with with key ring, rotatable luminaire, set (2 pcs.) grey
68Z00006	Mounting bracket (metal) with expander suspension (L 600 mm), set (2 pcs.) zinc plated
68Z00017	Mounting bracket (plastic) with expander suspension (L 600 mm), rotatable luminaire, set (2 pcs.) grey
68Z00005	Mounting bracket (metal) with adjustable belt suspension (L 330-550 mm), set (2 pcs.) zinc plated
68Z00008	Mounting bracket (plastic) with adjustable belt suspension (L 330-550 mm), rotatable luminaire, set (2 pcs.) grey