



68P300ED-0002.4K



series: Tube light FARM Tube lights

Type of installation: Universal mounting system
 Type of Protection: IP 67
 Protection class: I
 Lamp: LED
 Dimensions: D 78, L 965
 Colour: grey

Protective tube plastic opal (PMMA), integrated dimmable electronic driver, 3 m power supply cable, 2 stainless steel mounting brackets (M8/M10) incl. stainless steel hanger bolts

electro-technics:

Electric Gear DALI
 System Power 33 W
 Voltage 220 - 240 V / 0 Hz, 50 - 60 Hz

Spezifikationen:

Power supply cable NYY-J
 Size power supply cable 5 x 1,5 mm²
 Length power supply cable 3 m
 Colour power supply cable black
 Lamp cover opal

testings:

Type of Protection IP 67
 Protection class I
 Filament test 750°C - 30 seconds
 Impact resistance IK08 (5 Joule)
 Safety Marks F-mark
 Other Marks WEEE mark
 Country Code Made in Germany

lamp 1:

Lamp LED
 Number of Lamps 3
 Wattage 14,00 W
 Socket without socket
 Colour Temperature 4000 K
 Colour rendering index (CRI) 80
 Lifespan 50000 h (L70/B50)

weights and measures:

Length L 965 mm
 Diameter D 78 mm
 Weight 3,31 kg

lighting technology:

Luminaire flux 4.400 lm