



70-2000-0006



series: BEAM

Type of installation: portable
 Type of Protection: IP 65
 Protection class: II
 Lamp: LED
 Dimensions: L 352, B 223, H 357
 Colour: blue

Housing plastic (polycarbonate, edge guard made of soft thermoplastic elastomer TPE), cover plastic opal (polycarbonate), retractable stainless steel mounting hook with safeguard, second cable entry optional (through-wiring option), 3 m power supply cable with mains plug

electro-technics:

Electric Gear Converter
 System Power 47 W
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour handle black
 Power supply cable H07RN-F
 Size power supply cable 2 x 1,0 mm²
 Length power supply cable 3 m
 Colour power supply cable black
 Connector systems E+F, Konturenst. (CEE 7/17)
 Lamp cover opal

testings:

Type of Protection IP 65
 Protection class II
 Filament test 850°C - 30 seconds
 Impact resistance IK06 (1 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code nicht verwenden!

lamp 1:

Lamp LED
 Number of Lamps 1
 Wattage 43,00 W
 Socket without socket
 Colour Temperature 5000 K
 Colour rendering index (CRI) 80
 Lifespan 30000 h

weights and measures:

Length L 352 mm
 Width B 223 mm
 Height H 357 mm
 Weight 1,838 kg

lighting technology:

Luminaire flux 4.500 lm