



70-2000-0006

series: BEAM Compact lights



Type of installation: portable
Type of Protection: IP 65
Protection class: II
Lamp: LED
Dimensions: L 352, B 223, H 357
Colour: blue

Housing plastic (polycarbonate, edge guard made of soft thermoplastic elastomer TPE), cover plastic opal (polycarbonate), retractable stainless steel mounting hook with safeguard, second cable entry optional (through-wiring option), 3 m power supply cable with mains plug

electro-technics:

System power 47 W
Electric Gear Converter
Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour handle black
Power supply cable H07RN-F
Size power supply cable 2 x 1,0 mm²
Length power supply cable 3 m
Colour power supply cable black
Connector systems E+F, Konturenst. (CEE 7/17)
Lamp cover opal

testings:

Type of Protection IP 65
Protection class II
Filament test 850°C - 30 seconds
Impact resistance IK06 (1 Joule)
Safety Marks D-mark
Other Marks WEEE mark
Country Code nicht verwenden!

lamp 1:

Lamp LED
Number of Lamps 1
Colour Temperature 5000 K
Lifespan 30000 h
Rated luminous flux 4500 lm
Colour rendering index (CRI) 80

weights and measures:

Length L 352 mm
Width B 223 mm
Height H 357 mm
Weight 1,838 kg