



# 70-2000-0006

series: BEAM Compact lights



Type of installation: portable  
 Type of Protection: IP 65  
 Protection class: II  
 Lamp: LED  
 Dimensions: L 352, B 223, H 357  
 Colour: blue

Housing plastic (polycarbonate, edge guard made of soft thermoplastic elastomer TPE), cover plastic opal (polycarbonate), retractable stainless steel mounting hook with safeguard, second cable entry optional (through-wiring option), 3 m power supply cable with mains plug

## electro-technics:

System power 47 W  
 Electric Gear Converter  
 Voltage 220 - 240 V / 50 - 60 Hz

## Spezifikationen:

Colour handle black  
 Power supply cable H07RN-F  
 Size power supply cable 2 x 1,0 mm<sup>2</sup>  
 Length power supply cable 3 m  
 Colour power supply cable black  
 Connector systems E+F, Konturenst. (CEE 7/17)  
 Lamp cover opal

## testings:

Type of Protection IP 65  
 Protection class II  
 Filament test 850°C - 30 seconds  
 Impact resistance IK06 (1 Joule)  
 Safety Marks D-mark  
 Other Marks WEEE mark  
 Country Code nicht verwenden!

## lamp 1:

Lamp LED  
 Number of Lamps 1  
 Colour Temperature 5000 K  
 Colour rendering index (CRI) 80  
 Lifespan 30000 h  
 Rated luminous flux 4500 lm

## weights and measures:

Length L 352 mm  
 Width B 223 mm  
 Height H 357 mm  
 Weight 1,838 kg