



# 70F02901-0014



series: THORIX II Flex Floodlights

Type of installation: portable  
Type of Protection: IP 66  
Protection class: I  
Lamp: LED  
Dimensions: L 446, B 172, H 334  
Colour: silver metallic

Universal LED spotlight for mounting on a tripod or standing on the ground, housing: aluminium, silver-grey, powder-coated, stand: steel, silver-grey, powder-coated with 4 rubber feet, robust carry handle made of black plastic, lamp head finely adjustable in 6 ° steps, transparent PC cover with optical lens system, integrated DIN spigot adapter in accordance with DIN 14640.

## electro-technics:

System power 180 W  
Electric Gear Converter  
Voltage 220 - 240 V / 50 - 60 Hz

## Spezifikationen:

Colour handle black  
Power supply cable H07RN-F  
Size power supply cable 3 x 1,5 mm<sup>2</sup>  
Length power supply cable 10 m  
Colour power supply cable black  
Connector systems Typ E+F, Schuko IP68 (CEE 7/7)  
Lamp cover clear

## testings:

Type of Protection IP 66  
Protection class I  
Impact resistance IK08 (5 Joule)  
Safety Marks F-mark  
Other Marks WEEE mark  
Country Code Made in Germany

## lamp 1:

Number of Lamps 2  
Colour Temperature 5000 K  
Lamp LED  
Colour rendering index (CRI) 80  
Lifespan 50000 h (L80/B10)  
Luminaire Beam Angle 90°  
Rated luminous flux 24000 lm

## weights and measures:

Length L 446 mm  
Width B 172 mm  
Height H 334 mm  
Weight 8,785 kg