



# 70F03301-0014



series: THORIX II Flex Floodlights

Type of installation: portable  
 Type of Protection: IP 66  
 Protection class: I  
 Lamp: LED  
 Dimensions: L 446, B 172, H 419  
 Colour: silver metallic

Universal LED spotlight for mounting on a tripod or standing on the ground, housing: aluminium, silver-grey, powder-coated, stand: steel, silver-grey, powder-coated with 4 rubber feet, robust carry handle made of black plastic, lamp head finely adjustable in 6 ° steps, transparent PC cover with optical lens system, integrated DIN spigot adapter in accordance with DIN 14640.

## electro-technics:

System power 265 W  
 Electric Gear Converter  
 Voltage 220 - 240 V / 50 - 60 Hz

## Spezifikationen:

Colour handle black  
 Power supply cable H07RN-F  
 Size power supply cable 3 x 1,5 mm<sup>2</sup>  
 Length power supply cable 10 m  
 Colour power supply cable black  
 Connector systems Typ E+F, Schuko IP68 (CEE 7/7)  
 Lamp cover clear

## testings:

Type of Protection IP 66  
 Protection class I  
 Impact resistance IK08 (5 Joule)  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

## lamp 1:

Colour Temperature 5000 K  
 Lamp LED  
 Lifespan 50000 h (L80/B10)  
 Luminaire Beam Angle 30°  
 Rated luminous flux 35000 lm  
 Number of Lamps 3  
 Colour rendering index (CRI) 80

## weights and measures:

Length L 446 mm  
 Width B 172 mm  
 Height H 419 mm  
 Weight 11,513 kg