



70F03901-0014

series: THORIX II Flex Floodlights



Type of installation: portable
Type of Protection: IP 66
Protection class: I
Lamp: LED
Dimensions: L 446, B 172, H 419
Colour: silver metallic

Universal LED spotlight for mounting on a tripod or standing on the ground, housing: aluminium, silver-grey, powder-coated, stand: steel, silver-grey, powder-coated with 4 rubber feet, robust carry handle made of black plastic, lamp head finely adjustable in 6 ° steps, transparent PC cover with optical lens system, integrated DIN spigot adapter in accordance with DIN 14640.

electro-technics:

System power 265 W
Electric Gear Converter
Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour handle black
Power supply cable H07RN-F
Size power supply cable 3 x 1,5 mm²
Length power supply cable 10 m
Colour power supply cable black
Connector systems Typ E+F, Schuko IP68 (CEE 7/7)
Lamp cover clear

testings:

Type of Protection IP 66
Protection class I
Impact resistance IK08 (5 Joule)
Safety Marks F-mark
Other Marks WEEE mark
Country Code Made in Germany

lamp 1:

Colour Temperature 5000 K
Lamp LED
Lifespan 50000 h (L80/B10)
Luminaire Beam Angle 90°
Rated luminous flux 35000 lm
Number of Lamps 3
Colour rendering index (CRI) 80

weights and measures:

Length L 446 mm
Width B 172 mm
Height H 419 mm
Weight 11,513 kg