



70F03901-0014



series: THORIX II Flex Floodlights

Type of installation: portable
 Type of Protection: IP 66
 Protection class: I
 Lamp: LED
 Dimensions: L 446, B 172, H 419
 Colour: silver metallic

Universal LED spotlight for mounting on a tripod or standing on the ground, housing: aluminium, silver-grey, powder-coated, stand: steel, silver-grey, powder-coated with 4 rubber feet, robust carry handle made of black plastic, lamp head finely adjustable in 6 ° steps, transparent PC cover with optical lens system, integrated DIN spigot adapter in accordance with DIN 14640.

electro-technics:

Electric Gear Converter
 Voltage 220 - 240 V / 50 - 60 Hz
 System Power 265 W

Spezifikationen:

Colour handle black
 Power supply cable H07RN-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 10 m
 Colour power supply cable black
 Connector systems Typ E+F, Schuko IP68 (CEE 7/7)
 Lamp cover clear

testings:

Type of Protection IP 66
 Protection class I
 Impact resistance IK08 (5 Joule)
 Safety Marks F-mark
 Other Marks WEEE mark
 Country Code Made in Germany

lamp 1:

Number of Lamps 3
 Lamp LED
 Wattage 92,20 W
 Socket without socket
 Colour rendering index (CRI) 80
 Colour Temperature 5000 K
 Lifespan 50000 h (L80/B10)
 Luminaire Beam Angle 90°

weights and measures:

Length L 446 mm
 Width B 172 mm
 Height H 419 mm
 Weight 11,513 kg

lighting technology:

Luminaire flux 35.000 lm