



70FD2301-0014



series: THORIX II Flex Floodlights

Type of installation: portable
Type of Protection: IP 66
Protection class: I
Lamp: LED
Dimensions: L 446, B 172, H 334
Colour: silver metallic

Universal LED spotlight for mounting on a tripod or standing on the ground, housing: aluminium, silver-grey, powder-coated, stand: steel, silver-grey, powder-coated with 4 rubber feet, robust carry handle made of black plastic, lamp head finely adjustable in 6 ° steps, transparent PC cover with optical lens system, integrated DIN spigot adapter in accordance with DIN 14640.

electro-technics:

System power 180 W
Electric Gear Converter, dimmable, 1-10V
Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour handle black
Power supply cable H07BQ-F
Size power supply cable 3 x 1,5 mm²
Length power supply cable 10 m
Colour power supply cable yellow
Additional functions with switch
Connector systems Typ E+F, Schuko IP68 (CEE 7/7)
Lamp cover clear

testings:

Type of Protection IP 66
Protection class I
Impact resistance IK08 (5 Joule)
Safety Marks F-mark
Other Marks WEEE mark
Country Code Made in Germany

lamp 1:

Colour Temperature 5000 K
Lamp LED
Lifespan 50000 h (L80/B10)
Luminaire Beam Angle 30°
Rated luminous flux 24000 lm
Number of Lamps 2
Colour rendering index (CRI) 80

weights and measures:

Length L 446 mm
Width B 172 mm
Height H 334 mm
Weight 8,934 kg