



70T029Z0-0014



series: THORIX II

Type of installation: Pole mounting, Universal mounting system
Type of Protection: IP 66
Protection class: I
Lamp: LED
Dimensions: L 432, B 122, H 265
Colour: silver metallic

LED spotlights for wall, ceiling and pole mounting, weatherproof aluminium a metallic silver-grey, luminaire head can be finely adjusted in 6° steps for optimal positioning, clear, impact-resistant polycarbonate cover with lens optics, 1 m flexible H07RN-F connecting cable.

electro-technics:

System power 180 W
Electric Gear Converter
Voltage 220 - 240 V / 50 Hz, 60 Hz

Spezifikationen:

Power supply cable H07RN-F
Length power supply cable 1 m
Colour power supply cable black
Lamp cover clear

testings:

Type of Protection IP 66
Protection class I
Filament test 850 °C
Impact resistance IK08 (5 Joule)
Safety Marks F-mark
Other Marks WEEE mark
Country Code Made in Germany

lamp 1:

Colour Temperature 5000 K
Lamp LED
Lifespan 50000 h (L80/B10)
Luminaire Beam Angle 90°
Rated luminous flux 24000 lm
Number of Lamps 2
Colour rendering index (CRI) 80

weights and measures:

Length L 432 mm
Width B 122 mm
Height H 265 mm
Weight 6,12 kg

accessories

95-0281-0014 Glare shield (2- to 6-module) silver coloured
95-0283-0001 Mains junction box
95-0285-0001 Interception rope with snap hook