



70T033Z0-0014



series: THORIX II

Type of installation: Pole mounting, Universal mounting system
Type of Protection: IP 66
Protection class: I
Lamp: LED
Dimensions: L 434, B 122, H 351
Colour: silver metallic

LED spotlights for wall, ceiling and pole mounting, weatherproof aluminium a metallic silver-grey, luminaire head can be finely adjusted in 6° steps for optimal positioning, clear, impact-resistant polycarbonate cover with lens optics, 1 m flexible H07RN-F connecting cable.

electro-technics:

Electric Gear Converter
Voltage 220 - 240 V / 50 Hz, 60 Hz
System Power 265 W

Spezifikationen:

Power supply cable H07RN-F
Length power supply cable 1 m
Colour power supply cable black
Lamp cover clear

testings:

Type of Protection IP 66
Protection class I
Filament test 850 °C
Impact resistance IK08 (5 Joule)
Safety Marks F-mark
Other Marks WEEE mark
Country Code Made in Germany

lamp 1:

Number of Lamps 3
Lamp LED
Wattage 92,20 W
Socket without socket
Colour rendering index (CRI) 80
Colour Temperature 5000 K
Lifespan 50000 h (L80/B10)
Luminaire Beam Angle 30°

weights and measures:

Length L 434 mm
Width B 122 mm
Height H 351 mm
Weight 8,831 kg

lighting technology:

Luminaire flux 35.000 lm

accessories

95-0281-0014 Glare shield (2- to 6-module) silver coloured
95-0283-0001 Mains junction box
95-0285-0001 Interception rope with snap hook