



# 70T066Z0-0014



series: THORIX II

Type of installation: Pole mounting, Universal mounting system  
Type of Protection: IP 66  
Protection class: I  
Lamp: LED  
Dimensions: L 459, B 122, H 678  
Colour: silver metallic

LED spotlights for wall, ceiling and pole mounting, weatherproof aluminium a metallic silver-grey, luminaire head can be finely adjusted in 6° steps for optimal positioning, clear, impact-resistant polycarbonate cover with lens optics, 1 m flexible H07RN-F connecting cable.

## electro-technics:

Electric Gear Converter  
Voltage 220 - 240 V / 50 Hz, 60 Hz  
System Power 535 W

## Spezifikationen:

Power supply cable H07RN-F  
Length power supply cable 1 m  
Colour power supply cable black  
Lamp cover clear

## testings:

Type of Protection IP 66  
Protection class I  
Filament test 850 °C  
Impact resistance IK08 (5 Joule)  
Safety Marks F-mark  
Other Marks WEEE mark  
Country Code Made in Germany

## lamp 1:

Number of Lamps 6  
Lamp LED  
Wattage 92,20 W  
Socket without socket  
Colour rendering index (CRI) 80  
Colour Temperature 5000 K  
Lifespan 50000 h (L80/B10)  
Luminaire Beam Angle 60°

## weights and measures:

Length L 459 mm  
Width B 122 mm  
Height H 678 mm  
Weight 15,28 kg

## lighting technology:

Luminaire flux 70.000 lm

## accessories

95-0281-0014 Glare shield (2- to 6-module) silver coloured  
95-0283-0001 Mains junction box  
95-0285-0001 Interception rope with snap hook