



# 70T0C9Z0-0014



series: THORIX II

Type of installation: Pole mounting, Universal mounting system  
Type of Protection: IP 65  
Protection class: I  
Lamp: LED  
Dimensions: L 809, B 122, H 683  
Colour: silver metallic

LED spotlights for wall, ceiling and pole mounting, weatherproof aluminium a metallic silver-grey, luminaire head can be finely adjusted in 6° steps for optimal positioning, clear, impact-resistant polycarbonate cover with lens optics, 1 m flexible H07RN-F connecting cable.

## electro-technics:

System power 1115 W  
Electric Gear Converter  
Voltage 220 - 240 V / 50 Hz, 60 Hz

## Spezifikationen:

Power supply cable H07RN-F  
Length power supply cable 1 m  
Colour power supply cable black  
Lamp cover clear

## testings:

Type of Protection IP 65  
Protection class I  
Filament test 850 °C  
Impact resistance IK08 (5 Joule)  
Safety Marks F-mark  
Other Marks WEEE mark  
Country Code Made in Germany

## lamp 1:

Colour Temperature 5000 K  
Lamp LED  
Lifespan 50000 h (L80/B10)  
Luminaire Beam Angle 90°  
Rated luminous flux 150000 lm  
Number of Lamps 12  
Colour rendering index (CRI) 80

## weights and measures:

Length L 809 mm  
Width B 122 mm  
Height H 683 mm  
Weight 31,89 kg

## accessories

95-0282-0014 Glare shield (8- to 12-module) silver coloured  
95-0283-0001 Mains junction box  
95-0285-0001 Interception rope with snap hook