



70T4C3Z0-0014



series: THORIX II

Type of installation: Pole mounting, Universal mounting system
Type of Protection: IP 65
Protection class: I
Lamp: LED
Dimensions: L 809, B 122, H 683
Colour: silver metallic

LED spotlights for wall, ceiling and pole mounting, weatherproof aluminium a metallic silver-grey, luminaire head can be finely adjusted in 6° steps for optimal positioning, clear, impact-resistant polycarbonate cover with lens optics, 1 m flexible H07RN-F connecting cable.

electro-technics:

System power 1115 W
Electric Gear Converter
Voltage 400 V / 50 Hz, 60 Hz

Spezifikationen:

Power supply cable H07RN-F
Length power supply cable 1 m
Colour power supply cable black
Lamp cover clear

testings:

Type of Protection IP 65
Protection class I
Filament test 850 °C
Impact resistance IK08 (5 Joule)
Safety Marks F-mark
Other Marks WEEE mark
Country Code Made in Germany

lamp 1:

Colour Temperature 5000 K
Lamp LED
Lifespan 50000 h (L80/B10)
Luminaire Beam Angle 30°
Rated luminous flux 150000 lm
Number of Lamps 12
Colour rendering index (CRI) 80

weights and measures:

Length L 809 mm
Width B 122 mm
Height H 683 mm
Weight 31,63 kg

accessories

95-0282-0014 Glare shield (8- to 12-module) silver coloured
95-0283-0001 Mains junction box
95-0284-0001 Mains surface-mounted plug (CEE, 16A, 6h, 3P+N +PE, IP67)
95-0285-0001 Interception rope with snap hook