



# 80C04000-0006



series: POWERCASE L

Type of installation: portable  
 Type of Protection: IP 65  
 Protection class: I  
 Lamp: LED  
 Dimensions: L 884, B 225, H 495  
 Colour: silver metallic

Aluminium / plastic housing, clear polycarbonate cover with lens optics, detachable power supply cable with mains plug and potentiometer (continuously dimmable 10-100%), incl. adapter for spigot (d=30 mm, DIN 14640) with the possibility of straight or 30° angled assembly, incl. protective cover

## electro-technics:

System power 775 W  
 Electric Gear Converter, dimmable, 1-10V  
 Voltage 220 - 240 V / 50 - 60 Hz

## Spezifikationen:

Colour handle Blue  
 Power supply cable H07BQ-F  
 Size power supply cable 3 x 1,5 mm<sup>2</sup>  
 Length power supply cable 10 m  
 Colour power supply cable yellow  
 Additional functions with switch  
 Lamp cover clear  
 Connector systems Typ E+F, Schuko (CEE 7/7)

## testings:

Type of Protection IP 65  
 Protection class I  
 Impact resistance IK08 (5 Joule)  
 Safety Marks F-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

## lamp 1:

Rated luminous flux 100500 / 102200 lm  
 Lamp LED  
 Colour rendering index (CRI) 80  
 Colour Temperature 5000 K  
 Number of Lamps 8  
 Lifespan 50000 h (L80/B10)

## weights and measures:

Length L 884 mm  
 Width B 225 mm  
 Height H 495 mm  
 Weight 20,4 kg

## accessories

95-0060-0014 Crank tripod Premium, incl. Tripod adapter 28 mm / 30 mm (DIN 14640) chrome, smooth finish  
 95-0060-0014 Crank tripod Premium, incl. Tripod adapter 28 mm / 30 mm (DIN 14640), bracing set and carrier box chrome, smooth finish  
 95-0294-0014 Kurbel-Stativ Lightmaxx chrome, smooth finish  
 95-0254-0014 Tripod adapter, 28 mm / 30 mm (DIN 14640) stainless steel  
 95-0265-0040 Carrier box for Tripod "Premium", wood, 2 carrier handles beige  
 95-0266-0001 Rubberized joint feet for Crank tripod 'Premium' (Set 3x) black  
 95-0267-0001 Bracing set, 3x rope cord and peg blank  
 95-0227-0001 Belt strap incl. snap hook (set = 2 pieces), for suspended mounting grey  
 95-80C300-0000 Power supply cable for POWERCASE L, Luminaire function: not dimmable, Plug CEE 7/7 (Type E+F), IPx4  
 95-80C301-0000 Power supply cable for POWERCASE L, Luminaire function: not dimmable, Plug CEE 7/7 (Type E+F), IPx4  
 95-80C400-0000 Power supply cable for POWERCASE L, Luminaire function: dimmable, Plug CEE 7/7 (Type E+F), IPx4  
 95-80C401-0000 Power supply cable for POWERCASE L, Luminaire function: not dimmable, Plug CEE 7/7 (Type E+F), IPx4  
 95-80C500-0000 Power supply cable for POWERCASE L, Luminaire function: separately dimmable on both sides, Plug CEE 7/7 (Type E+F), IPx4  
 95-80C501-0000 Power supply cable for POWERCASE L, Luminaire function: separately dimmable on both sides, Plug CEE 7/7 (Type E+F), IP68  
 95-80CB00-0000 Power supply cable for POWERCASE L, Fonction luminaire : Bluetooth, Plug CEE 7/7 (Type E+F), IPx4  
 95-80CB01-0000 Power supply cable for POWERCASE L, Fonction luminaire : Bluetooth, Plug CEE 7/7 (Type E+F), IP68