



80C05006-0006



series: POWERCASE L

Type of installation: portable
 Type of Protection: IP 65
 Protection class: I
 Lamp: LED
 Dimensions: L 884, B 225, H 495
 Colour: silver metallic

Aluminium / plastic housing, clear polycarbonate cover with lens optics, detachable power supply cable with mains plug and double potentiometer (both halves of the luminaire separately and continuously dimmable 10-100%), incl. adapter for spigot (d=30 mm, DIN 14640) with the possibility of straight or 30° angled assembly, incl. protective cover

electro-technics:

System power 775 W
 Electric Gear Converter, dimmable, 1-10V
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour handle Blue
 Power supply cable H07BQ-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 10 m
 Colour power supply cable yellow
 Additional functions with switch
 Connector systems CEE-6h
 Lamp cover clear

testings:

Type of Protection IP 65
 Protection class I
 Impact resistance IK08 (5 Joule)
 Safety Marks F-mark
 Other Marks WEEE mark
 Country Code Made in Germany

lamp 1:

Rated luminous flux 100500 / 102200 lm
 Colour Temperature 5000 K
 Number of Lamps 8
 Lamp LED
 Colour rendering index (CRI) 80
 Lifespan 50000 h (L80/B10)

weights and measures:

Length L 884 mm
 Width B 225 mm
 Height H 495 mm
 Weight 20,4 kg

accessories

- 95-0060-0014 Crank tripod Premium, incl. Tripod adapter 28 mm / 30 mm (DIN 14640) chrome, smooth finish
- 95-0060-0014 Crank tripod Premium, incl. Tripod adapter 28 mm / 30 mm (DIN 14640), bracing set and carrier box chrome, smooth finish
- 95-0294-0014 Kurbel-Stativ Lightmaxx chrome, smooth finish
- 95-0254-0014 Tripod adapter, 28 mm / 30 mm (DIN 14640) stainless steel
- 95-0265-0040 Carrier box for telescopic tripod 'Premium', wood, 2 carrier handles beige
- 95-0266-0001 Rubberized joint feet for Crank tripod 'Premium' (Set 3x) black
- 95-0267-0001 Bracing set, 3x rope cord and peg blank
- 95-0227-0001 Belt strap incl. snap hook (set = 2 pieces), for suspended mounting grey
- 95-80C300-0000 Power supply cable for POWERCASE L, Luminaire function: not dimmable, Plug CEE 7/7 (Type E+F), IPx4
- 95-80C301-0000 Power supply cable for POWERCASE L, Luminaire function: not dimmable, Plug CEE 7/7 (Type E+F), IPx4
- 95-80C400-0000 Power supply cable for POWERCASE L, Luminaire function: dimmable, Plug CEE 7/7 (Type E+F), IPx4
- 95-80C401-0000 Power supply cable for POWERCASE L, Luminaire function: not dimmable, Plug CEE 7/7 (Type E+F), IPx4
- 95-80C500-0000 Power supply cable for POWERCASE L, Luminaire function: separately dimmable on both sides, Plug CEE 7/7 (Type E+F), IPx4
- 95-80C501-0000 Power supply cable for POWERCASE L, Luminaire function: separately dimmable on both sides, Plug CEE 7/7 (Type E+F), IP68
- 95-80CB00-0000 Power supply cable for POWERCASE L, Fonction luminaire : Bluetooth, Plug CEE 7/7 (Type E+F), IPx4
- 95-80CB01-0000 Power supply cable for POWERCASE L, Fonction luminaire : Bluetooth, Plug CEE 7/7 (Type E+F), IP68