



80P01006-0006



series: POWERDISK modular and linear luminaires

Type of installation: portable
 Type of Protection: IP 65
 Protection class: I
 Lamp: LED
 Dimensions: L 750, B 630, H 250
 Colour: white

Housing aluminum / stainless steel, cover plastic (polycarbonate, opal), dimmable 1...100, power supply cable with mains plug and switch, incl. adapter for Spigot 30mm conforming to DIN 14640

electro-technics:

System power 380 W
 Electric Gear Touch-Dim converter
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Power supply cable H07BQ-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 10 m
 Colour power supply cable yellow
 Additional functions with switch
 Connector systems CEE-6h
 Lamp cover opal

testings:

Type of Protection IP 65
 Protection class I
 Impact resistance IK10 (20 Joule)
 Safety Marks F-mark
 Other Marks WEEE mark
 Country Code Made in Germany

lamp 1:

Lamp LED
 Number of Lamps 24
 Colour Temperature 5000 K
 Lifespan 100000 h (L80/B10)
 Rated luminous flux 57000 lm
 Colour rendering index (CRI) 82

weights and measures:

Length L 750 mm
 Width B 630 mm
 Height H 250 mm
 Weight 15,7 kg

accessories

- 95-0254-0014 Tripod adapter, 28 mm / 30 mm (DIN 14640) stainless steel
- 95-0060-0014 Crank tripod Premium, incl. Tripod adapter 28 mm / 30 mm (DIN 14640) chrome, smooth finish
- 95-0255-0014 Adapter Ceiling mounting stainless steel
- 95-0256-0040 **Transport Box** beige
- 95-0257-0014 Tripod "Professionell", 4.70m, stainless steel stainless steel
- 95-0259-0001 **Carrier bag for "POWERDISK"**, handles, shoulder belt and transport rollers black
- 95-0267-0001 Bracing set, 3x rope cord and peg blank
- 95-0060-0014 **Crank tripod Premium**, incl. Tripod adapter 28 mm / 30 mm (DIN 14640), bracing set and carrier box chrome, smooth finish
- 95-0257-0014 **Set Tripod "Professionell"**, includes Tripod "Professionell and carrier box stainless steel