



83-01000-0006



series: GLADIATOR SL I Compact lights

Type of installation: portable
 Type of Protection: IP 66
 Protection class: II
 Lamp: LED
 Dimensions: L 283, B 272, H 104
 Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), power supply cable with mains plug

electro-technics:

System power 40 W
 Electric Gear Converter
 Voltage 220 - 240 V / 50 Hz, 60 Hz

Spezifikationen:

Colour TPE blue
 Colour handle black
 Length power supply cable 5 m
 Size power supply cable 2 x 1,0 mm²
 Power supply cable H07RN-F
 Colour power supply cable black
 Lamp cover opal

testings:

Type of Protection IP 66
 Protection class II
 Filament test 850°C - 30 seconds
 Impact resistance IK08 (5 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code CE

lamp 1:

Rated luminous flux 4000 lm
 Number of Lamps 1
 Colour Temperature 5000 K
 Lamp LED
 Lifespan
 Colour rendering index (CRI) 80

weights and measures:

Length L 283 mm
 Width B 272 mm
 Height H 104 mm
 Weight 2,31 kg

accessories

- 95-0170-0001 Tripod Standard, without castors, set with mounting rail for 1 work light zinc plated
- 95-0171-0001 Tripod Standard, with castors, set with mounting rail for 1 work light zinc plated
- 95-0172-0001 Tripod Standard, without castors, set with mounting rail for 2 work lights zinc plated
- 95-0173-0001 Tripod Standard, with castors, set with mounting rail for 2 work lights zinc plated
- 95-0270-0001 Magnet set, for attachment to the threaded bushes in the handle black
- 95-0268-0001 Mounting rail for one GLADIATOR SL I or SL II black
- 95-0269-0001 Mounting rail for 2x GLADIATOR SL I or SL II black
- 95-0061-0001 Tripod 'Profi', 3-part, extendable up to 3.20 m zinc plated
- 95-0290-0006 Transport bag for work light blue