



83-02200-0006



series: GLADIATOR SL II Workplace luminaires

Type of installation: portable
 Type of Protection: IP 54
 Protection class: I
 Lamp: LED
 Dimensions: L 388, B 370, H 105
 Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), two sockets and switch, power supply cable with mains plug

electro-technics:

Electric Gear Converter
 Voltage 220 - 240 V / 50 - 60 Hz
 System Power 75 W

Spezifikationen:

Colour TPE blue
 Colour handle black
 Power supply cable H07RN-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Additional functions with switch
 Connector systems F (CEE 7/3)
 Socket outlets 2
 Lamp cover opal

testings:

Type of Protection IP 54
 Protection class I
 Filament test 850°C - 30 seconds
 Impact resistance IK08 (5 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code CE

lamp 1:

Number of Lamps 1
 Lamp LED
 Wattage 70,00 W
 Socket without socket
 Colour rendering index (CRI) 80
 Colour Temperature 5000 K
 Lifespan

weights and measures:

Length L 388 mm
 Width B 370 mm
 Height H 105 mm
 Weight 3,87 kg

lighting technology:

Luminaire flux 8.000 lm

accessories

- 95-0170-0001 Tripod Standard, without castors, set with mounting rail for 1 work light zinc plated
- 95-0171-0001 Tripod Standard, with castors, set with mounting rail for 1 work light zinc plated
- 95-0172-0001 Tripod Standard, without castors, set with mounting rail for 2 work lights zinc plated
- 95-0173-0001 Tripod Standard, with castors, set with mounting rail for 2 work lights zinc plated
- 95-0268-0001 Mounting rail for one GLADIATOR SL I or SL II black
- 95-0269-0001 Mounting rail for 2x GLADIATOR SL I or SL II black
- 95-0061-0001 Tripod 'Profi', 3-part, extendable up to 3.20 m zinc plated
- 95-0290-0006 Transport bag for work light blue