



83-022B0-0006



series: GLADIATOR SL II Compact lights

Type of installation: portable
 Type of Protection: IP 44
 Protection class: I
 Lamp: LED
 Dimensions: L 388, B 370, H 105
 Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), two sockets and switch, power supply cable with mains plug

electro-technics:

System power 75 W
 Electric Gear Converter
 Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour TPE blue
 Colour handle black
 Length power supply cable 5 m
 Size power supply cable 3 x 1,5 mm²
 Power supply cable H07RN-F
 Colour power supply cable black
 Additional functions with switch
 Socket outlets 2
 Connector systems Typ E (CEE 7/5)
 Lamp cover opal

testings:

Type of Protection IP 44
 Protection class I
 Filament test 850°C - 30 seconds
 Impact resistance IK08 (5 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code CE

lamp 1:

Rated luminous flux 8000 lm
 Number of Lamps 1
 Colour Temperature 5000 K
 Lamp LED
 Lifespan
 Colour rendering index (CRI) 80

weights and measures:

Length L 388 mm
 Width B 370 mm
 Height H 105 mm
 Weight 3,87 kg

accessories

- 95-0170-0001 Tripod Standard, without castors, set with mounting rail for 1 work light zinc plated
- 95-0171-0001 Tripod Standard, with castors, set with mounting rail for 1 work light zinc plated
- 95-0172-0001 Tripod Standard, without castors, set with mounting rail for 2 work lights zinc plated
- 95-0173-0001 Tripod Standard, with castors, set with mounting rail for 2 work lights zinc plated
- 95-0268-0001 Mounting rail for one GLADIATOR SL I or SL II black
- 95-0269-0001 Mounting rail for 2x GLADIATOR SL I or SL II black
- 95-0061-0001 Tripod 'Profi', 3-part, extendable up to 3.20 m zinc plated
- 95-0290-0006 Transport bag for work light blue