

electro-technics:

System power 36 W
Electric Gear Converter

Voltage 220 - 240 V / 50 - 60 Hz

Spezifikationen:

Colour TPE blue
Colour handle black
Length power supply cable 5 m
Size power supply cable 2 x 1,0 mm²

Power supply cable H05RN-F
Colour power supply cable black
Lamp cover opal

testings:

Type of Protection IP 66 Protection class III

Filament test 850°C - 30 seconds
Impact resistance IK07 (2 Joule)
Safety Marks D-mark
Other Marks WEEE mark
Country Code Made in Germany

lamp 1:

Rated luminous flux 4000 lm Number of Lamps 1

Colour Temperature 5000 K Lamp LED

Lifespan

Colour rendering index (CRI) 80

weights and measures:

 Length L
 283 mm

 Width B
 272 mm

 Height H
 104 mm

 Weight
 2,4 kg

83-A1043-0006



series: GLADIATOR SL I Accu Compact lights

Type of installation: portable
Type of Protection: IP 66
Protection class: III
Lamp: LED

Dimensions: L 283, B 272, H 104

Colour: black

Mobile, mains-independent battery-operated work light. Impact-resistant and break-proof 2-component plastic housing. Edge protection and handle with soft plastic (thermoplastic elastomer - TPE). Cover opal, made of impact- and break-resistant plastic (polycarbonate). Beam angle adjustable with handle, plastic (ABS). Ergonomically placed control panel with buttons for on/off and dimming in steps of 5, 10, 20, 50 and 100% and LED display of battery capacity and operating time. Modern Li-Ion battery with 27 Wh for up to 10 hours of operation. Includes plug-in power supply for charging (3.5 h) or mains operation with a 5 m supply cable.

accessories

95-0290-0006 Transport bag for work light blue

95-0170-0001 Tripod Standard, without castors, set with mounting rail

for 1 work light zinc plated

95-0171-0001 Tripod Standard, with castors, set with mounting rail for

1 work light zinc plated

95-0172-0001 Tripod Standard, without castors, seit with mounting

rail for 2 work lights zinc plated

95-0173-0001 Tripod Standard, with castors, set with mounting rail for

2 work lights zinc plated

95-0270-0001 Magnet set, for attachment to the threaded bushes in

the handle black