

electro-technics:

System power Electric Gear Voltage 36 W Converter 220 - 240 V / 50 - 60 Hz

blue

black

black

opal

2 x 1,0 mm²

5 m H05RN-F

Spezifikationen:

Colour TPE Colour handle Length power supply cable Power supply cable Size power supply cable Colour power supply cable Lamp cover

testings:

Type of Protection	IP 66
Protection class	
Filament test	850°C - 30 seconds
Impact resistance	IK07 (2 Joule)
Safety Marks	D-mark
Other Marks	WEEE mark
Country Code	Made in Germany
lamp 1:	
Rated luminous flux	4000 lm
Colour Temperature	5000 K

Colour Temperature	5000
Number of Lamps	1
Lamp	LED
Lifespan	
Colour rendering index (CRI)	80

weights and measures:

Length L	283 mm
Width B	272 mm
Height H	104 mm
Weight	2,4 kg

83-A1043-0006



series: GLADIATOR SL I Accu Compact lights

Type of installation:portableType of Protection:IP 66Protection class:IIILamp:LEDDimensions:L 283, B 272, H 104Colour:black

Mobile, mains-independent battery-operated work light. Impactresistant and break-proof 2-component plastic housing. Edge protection and handle with soft plastic (thermoplastic elastomer - TPE). Cover opal, made of impact- and break-resistant plastic (polycarbonate). Beam angle adjustable with handle, plastic (ABS). Ergonomically placed control panel with buttons for on/off and dimming in steps of 5, 10, 20, 50 and 100% and LED display of battery capacity and operating time. Modern Li-Ion battery with 27 Wh for up to 10 hours of operation. Includes plug-in power supply for charging (3.5 h) or mains operation with a 5 m supply cable. **accessories**

95-0290-0006	Transport bag for work light blue
95-0170-0001	Tripod Standard, without castors, set with mounting rail
	for 1 work light zinc plated
95-0171-0001	Tripod Standard, with castors, set with mounting rail for
	1 work light zinc plated
95-0172-0001	Tripod Standard, without castors, seit with mounting
	rail for 2 work lights zinc plated
95-0173-0001	Tripod Standard, with castors, set with mounting rail for
	2 work lights zinc plated
95-0270-0001	Magnet set, for attachment to the threaded bushes in
	the handle black