



83-B1200-0006



series: GLADIATOR SL I B18V Workplace luminaires

Type of installation: portable
 Type of Protection: IP 20
 Protection class: III
 Lamp: LED
 Dimensions: L 283, B 272, H 104
 Colour: black

Mobile, mains-independent battery-operated work light. Impact-resistant and break-proof 2-component plastic housing. Edge protection and handle with soft plastic. Uniform, soft and glare-reduced illumination thanks to multi-LED technology, opal cover and large light emission surface. Beam angle adjustable with handle, plastic (ABS). Suitable for use with Bosch Professional 18V exchangeable batteries. Supplied with Bosch GBA 18 V 5.0 Ah battery and Bosch GAL 18V-40 charger. Ergonomically placed control panel with buttons for on/off and dimming in steps of 10, 25, 50, 75 and 100%.

accessories

- 95-B1100-0001 Bosch battery GBA 18V 5Ah
- 95-B1200-0001 Charger Bosch GAL 18V-40
- 95-0170-0001 Tripod Standard, without castors, set with mounting rail for 1 work light zinc plated
- 95-0171-0001 Tripod Standard, with castors, set with mounting rail for 1 work light zinc plated
- 95-0172-0001 Tripod Standard, without castors, set with mounting rail for 2 work lights zinc plated
- 95-0173-0001 Tripod Standard, with castors, set with mounting rail for 2 work lights zinc plated
- 95-0270-0001 Magnet set, for attachment to the threaded bushes in the handle black
- 95-0268-0001 Mounting rail for one GLADIATOR SL I or SL II black
- 95-0269-0001 Mounting rail for 2x GLADIATOR SL I or SL II black
- 95-0061-0001 Tripod 'Profi', 3-part, extendable up to 3.20 m zinc plated
- 95-0290-0006 Transport bag for work light blue

electro-technics:

Electric Gear Converter
 Voltage 18 V / 0 Hz
 System Power 29 W

Spezifikationen:

Colour TPE blue
 Colour handle black
 Lamp cover opal

testings:

Type of Protection IP 20
 Protection class III
 Impact resistance IK08 (5 Joule)
 Other Marks WEEE mark

lamp 1:

Number of Lamps 1
 Lamp LED
 Wattage 27,00 W
 Socket without socket
 Colour rendering index (CRI) 80
 Colour Temperature 5000 K
 Lifespan 50000 h (L80/B10)

weights and measures:

Length L 283 mm
 Width B 272 mm
 Height H 104 mm
 Weight 2,76 kg

lighting technology:

Luminaire flux 4.000 lm