



88-0L101-0006



series: GLADIATOR II Workplace luminaires

Type of installation: portable
Type of Protection: IP 65
Protection class: I
Lamp: LED
Dimensions: L 320, B 305, H 110
Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), socket/s and switch, power supply cable with mains plug, incl. LED panel

electro-technics:

Electric Gear Converter
System Power 40 W
Voltage 230 V / 50 Hz

Spezifikationen:

Colour TPE blue
Colour handle black
Power supply cable H07RN-F
Size power supply cable 3 x 1,5 mm²
Length power supply cable 5 m
Colour power supply cable black
Additional functions with switch
Connector systems Typ F, Schuko IP68 (CEE 7/4)
Socket outlets 1
Lamp cover opal

testings:

Type of Protection IP 65
Protection class I
Filament test 850°C - 30 seconds
Impact resistance IK08 (5 Joule)
Safety Marks D-mark
Other Marks WEEE mark
Country Code Made in Germany

lamp 1:

Lamp LED
Number of Lamps 1
Wattage 36,00 W
Socket without socket
Colour Temperature 5000 K
Colour rendering index (CRI) 80
Lifespan 50000 h (L70/B50)

weights and measures:

Length L 320 mm
Width B 305 mm
Height H 110 mm
Weight 2,885 kg

lighting technology:

Luminaire flux 4.000 lm