



88-0L300-0006



series: GLADIATOR II Workplace luminaires

Type of installation: portable
 Type of Protection: IP 54
 Protection class: I
 Lamp: LED
 Dimensions: L 320, B 305, H 110
 Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), socket/s and switch, power supply cable with mains plug, incl. LED panel

electro-technics:

Electric Gear Converter
 System Power 40 W
 Voltage 220 - 240 V / 50 Hz, 60 Hz

Spezifikationen:

Colour TPE blue
 Colour handle black
 Power supply cable H07RN-F
 Size power supply cable 3 x 1,5 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Additional functions with switch
 Connector systems Typ F, Schuko (CEE 7/4)
 Socket outlets 3
 Lamp cover opal

testings:

Type of Protection IP 54
 Protection class I
 Filament test 850°C - 30 seconds
 Impact resistance IK08 (5 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code Made in Germany

lamp 1:

Lamp LED
 Number of Lamps 1
 Wattage 36,00 W
 Socket without socket
 Colour Temperature 5000 K
 Colour rendering index (CRI) 80
 Lifespan 50000 h (L70/B50)

weights and measures:

Length L 320 mm
 Width B 305 mm
 Height H 110 mm
 Weight 2,83 kg

lighting technology:

Luminaire flux 4.000 lm