



# 88-0L3B0-0006



series: GLADIATOR II Workplace luminaires

Type of installation: portable  
Type of Protection: IP 54  
Protection class: I  
Lamp: LED  
Dimensions: L 320, B 305, H 110  
Colour: blue

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), socket/s and switch, power supply cable with mains plug, incl. LED panel

## electro-technics:

Electric Gear Converter  
System Power 40 W  
Voltage 220 - 240 V / 50 - 60 Hz

## Spezifikationen:

Colour TPE blue  
Colour handle black  
Power supply cable H07RN-F  
Size power supply cable 3 x 1,5 mm<sup>2</sup>  
Length power supply cable 5 m  
Colour power supply cable black  
Additional functions with switch  
Connector systems Typ E (CEE 7/5)  
Socket outlets 3  
Lamp cover opal

## testings:

Type of Protection IP 54  
Protection class I  
Filament test 850°C - 30 seconds  
Impact resistance IK08 (5 Joule)  
Safety Marks D-mark  
Other Marks WEEE mark  
Country Code Made in Germany

## lamp 1:

Lamp LED  
Number of Lamps 1  
Wattage 36,00 W  
Socket without socket  
Colour Temperature 5000 K  
Colour rendering index (CRI) 80  
Lifespan 50000 h (L70/B50)

## weights and measures:

Length L 320 mm  
Width B 305 mm  
Height H 110 mm  
Weight 2,8 kg

## lighting technology:

Luminaire flux 4.000 lm