



88-5L050-0006



series: GLADIATOR II Compact lights

Type of installation: portable
 Type of Protection: IP 66
 Protection class: III
 Lamp: LED
 Dimensions: L 320, B 305, H 110
 Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), power supply cable with mains plug, incl. LED panel

electro-technics:

System power 41 W
 Electric Gear Converter
 Voltage 20 - 35 V / 50 - 60 Hz

Spezifikationen:

Colour TPE blue
 Colour handle black
 Power supply cable H07RN-F
 Size power supply cable 2 x 1,5 mm²
 Length power supply cable 5 m
 Colour power supply cable black
 Connector systems CEE 24VAC
 Lamp cover opal

testings:

Type of Protection IP 66
 Protection class III
 Filament test 850°C - 30 seconds
 Impact resistance IK08 (5 Joule)
 Safety Marks D-mark
 Other Marks WEEE mark
 Country Code Made in Germany

lamp 1:

Lamp LED
 Number of Lamps 1
 Colour Temperature 5000 K
 Colour rendering index (CRI) 80
 Lifespan 50000 h (L70/B50)
 Rated luminous flux 4000 lm

weights and measures:

Length L 320 mm
 Width B 305 mm
 Height H 110 mm
 Weight 2,47 kg