



# 88-6L060-0006



series: GLADIATOR II Compact lights

Type of installation: portable  
 Type of Protection: IP 44  
 Protection class: III  
 Lamp: LED  
 Dimensions: L 320, B 305, H 110  
 Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), power supply cable with mains plug, incl. LED panel

### electro-technics:

System power 41 W  
 Electric Gear Converter  
 Voltage 35 - 50 V / 50 Hz, 60 Hz

### Spezifikationen:

Colour TPE blue  
 Colour handle black  
 Power supply cable H07RN-F  
 Size power supply cable 2 x 1,5 mm<sup>2</sup>  
 Length power supply cable 5 m  
 Colour power supply cable black  
 Connector systems CEE 42VAC  
 Lamp cover opal

### testings:

Type of Protection IP 44  
 Protection class III  
 Filament test 850°C - 30 seconds  
 Impact resistance IK08 (5 Joule)  
 Safety Marks D-mark  
 Other Marks WEEE mark  
 Country Code Made in Germany

### lamp 1:

Lamp LED  
 Number of Lamps 1  
 Colour Temperature 5000 K  
 Lifespan 50000 h (L70/B50)  
 Rated luminous flux 4000 lm  
 Colour rendering index (CRI) 80

### weights and measures:

Length L 320 mm  
 Width B 305 mm  
 Height H 110 mm  
 Weight 2,5 kg