



# 88-6L060-0006



series: GLADIATOR II Workplace luminaires

Type of installation: portable  
Type of Protection: IP 44  
Protection class: III  
Lamp: LED  
Dimensions: L 320, B 305, H 110  
Colour: black

Housing plastic anthracite/blue (polycarbonate, edge guard made of soft thermoplastic elastomer - TPE), cover plastic opal (polycarbonate), handle plastic black (ABS), power supply cable with mains plug, incl. LED panel

## electro-technics:

Electric Gear Converter  
System Power 40 W  
Voltage 35 - 50 V / 50 Hz, 60 Hz

## Spezifikationen:

Colour TPE blue  
Colour handle black  
Power supply cable H07RN-F  
Size power supply cable 2 x 1,5 mm<sup>2</sup>  
Length power supply cable 5 m  
Colour power supply cable black  
Connector systems CEE 42VAC  
Lamp cover opal

## testings:

Type of Protection IP 44  
Protection class III  
Filament test 850°C - 30 seconds  
Impact resistance IK08 (5 Joule)  
Safety Marks D-mark  
Other Marks WEEE mark  
Country Code Made in Germany

## lamp 1:

Lamp LED  
Number of Lamps 1  
Wattage 37,50 W  
Socket without socket  
Colour Temperature 5000 K  
Colour rendering index (CRI) 80  
Lifespan 50000 h (L70/B50)

## weights and measures:

Length L 320 mm  
Width B 305 mm  
Height H 110 mm  
Weight 2,5 kg

## lighting technology:

Luminaire flux 4.000 lm